

**DK**

**throttle valves**



Ref. no.  
**228**

**9228**

**Prices without engine**

NW [mm]	Dimensions			Weight	Version															
					with spigot for lip sealing		Lip sealing		with spigot for lip sealing		Lip sealing		with spigot for lip sealing		Lip sealing		Add. charge Insulating shell		Add. charge Insulating shell	
	galvanized steel		galvanized steel		stainless steel material 1.4301		stainless steel material 1.4301		stainless steel material 1.4571		stainless steel material 1.4571		galvanized steel		stainless steel					
	1	2	1		2	1	2	1	2	1	2	1	2	1	2	25 mm	50 mm	25 mm	50 mm	
80	120	40	200	0,5 kg																
100	120	40	200	0,6 kg																
125	120	40	200	0,7 kg																
140	120	40	200	0,8 kg																
150	120	40	200	0,9 kg																
160	120	40	200	0,9 kg																
180	120	40	200	1,0 kg																
200	140	40	220	1,2 kg																
224	140	40	220	1,3 kg																
250	140	40	220	1,5 kg																
280	130	60	250	2,3 kg																
300	130	60	250	2,5 kg																
315	130	60	250	2,6 kg																
355	130	60	250	3,8 kg																
400	130	60	250	4,2 kg																
450	130	60	250	6,5 kg																
500	270	60	390	11,0 kg																
560	270	60	390	12,5 kg																
600	470	60	590	15,0 kg																
630	470	60	590	15,5 kg																

*Prices on request*

**Price setting:** All prices are exclusive of VAT, ex factory Friedrichsthal and without packaging. Our conditions of delivery and payment are valid.



Manufacturing tolerance for the length dimensions ± 5 mm

Aerotechnik E. Siegwart GmbH  
 Untere Hofwiesen • D-66299 Friedrichsthal  
 ☎ +49 (0) 6897/859-0 • 📠 +49 (0) 6897/859-150  
 www.aerotechnik.de • info@aerotechnik.de

**DK****throttle valves****Price list**

Ref. no.

**228****9228****Additional charge and actuator variants for electronic actuation****(Belimo)**

Size [mm]	Type		Torque [Nm]	Weight [kg]	Price
80 - 355	LM 230 A	LM 24 A	5	0,5	Prices
400 - 630	NM 230 A	NM 24 A	10	0,8	on request

Other electronic or pneumatic actuators on request.

**Specifications:**

Throttle valve, type: DKH, (DKM) manufactured by AEROTECHNIK E. Siegart

Housing made of galvanized steel - laser-welded, shaft feedthrough of the throttle disc is located in a maintenance-free and airtight screwing, airtightness of the push-fit ends with lip sealing according to DIN 12237 class D, operating temperature range: -15°C to + 100°C.

Order example:

Ref. no.	Size	Version	SV	Material	Electric motor	Pneumatic motor	Insulating shell
<b>9228</b>	<b>315</b>	<b>1</b>	<b>1</b>	<b>verzinkt</b>	<b>-</b>	<b>-</b>	<b>25</b>

**Prices without actuator**

Ref. no. 228

Sicke für Lippendichtung  
bead for lip sealing  
moulure pour joints à lèvres

Ref. no. 9228

Lippendichtung  
Joints à lèvres  
Lip sealing**Price setting:** All prices are exclusive of VAT, ex factory Friedrichsthal and without packaging. Our conditions of delivery and payment are valid.

Aerotechnik E. Siegart GmbH  
 Untere Hofwiesen • D-66299 Friedrichsthal  
 ☎ +49 (0) 6897/859-0 • 📠 +49 (0) 6897/859-150  
 www.aerotechnik.de • info@aerotechnik.de